

蒸氣老化壽命試驗機
Steam aging life tester



◎使用目的(Exclusive use of industry and use purpose)

- 半导体IC、电晶体、二极体、液晶LCD、晶片电阻电容、零组件产业
- 电子零件组金属接脚沾锡性试验前的老化加速寿命时间试验目的(蒸气老化寿命试验机)
- Semiconductor、Transistor、LCD、Resistance Chip、Capacitance Chip、Diode、Electronic component industry
- Life test for pins of electronic component industry be soaked with tin



◎控制系统(Control System)

OMRON E5AN	微电脑LED控制器(MICRO-computer LED controller)
TIMER	运转时间计时器(Operating Timer)
INDEX	运转指示器/故障指示器(Operating/Error Indicator)
START SW	启动运转开关(Operating Switch)
ERROR SW	故障解除开关(Error reset Switch)
POWER SW	控制电源开关(Power Switch)



◎测试篮尺寸(Test basket Dimension)

W:92mm d:285mm h:40mm

◎规格表(Specification table)

规格(Specification)	Standard Table Type
型号(Model)	FHT-B
升温时间(Heating time)	R.T.~98°C/60Min
控制器(Controller)	OmRON E5AN Mic-computer controller (Resolution:0.1°C)
温度稳定度/温度分布均匀度 (Temp. stability / Temp Uniformity)	± 0.5°C / ± 1.0°C
内外箱材料 (Internal、external material)	SUS#316 stainless steel by completely assembled structure
隔热材料 (Insulating material)	Frie protection glass wool
加热器 (Heater)	Insulation temperature heater (1.5 kw)
安全系统 (Security system)	Earth leakage breaker/Water shortage Protector/Error indicator
电源 (Power)	AC 220V 1φ 50/60Hz
安培 (Ampere)	7 A
重量 (Weight [KG])	60KG
测试篮 (Test basket)	4Sets
外箱尺寸(External dimension [W×D×H]mm)	820×560×440

※以上规格, 请以实体报价为主 (For above accessories, their actual specifications may vary).